

\*NOW STOCKED IN CD4MCu

### MOUNTING CONFIGURATIONS


**6NNT-RP-F Redi-Prime® Frame Mount**  
**6NNT-RP-EM Redi-Prime® Engine Mount**  
**6NNT-F Frame Mount**  
**6NNT-EM Engine Mount**  
**6NNT-CC Close-Coupled Mount**  
**6NNT-VM Vertical Mount**  
**6NNT-VF Vertical Frame Mount**

### STOCK MATERIALS

**All Iron, CD4MCu**

### OPERATING LEVELS

MAX FLOW:	<b>2750 GPM</b>	<b>173.5 L/S</b>
DISCHARGE SIZE:	<b>6"</b>	<b>15 cm</b>
SUCTION SIZE:	<b>6"</b>	<b>15 cm</b>
SOLIDS HANDLING:	<b>3"</b>	<b>7.6 cm</b>
MAX SPEED:	<b>2100 RPM</b>	<b>2100 RPM</b>
MAX HEAD:	<b>150'</b>	<b>46 m</b>



A typical picture of the pump is shown. Please contact StarTech Pump Company for further details. All information is approximate and for general guidance only.

Pump designed with StarTech's renowned quality and durability. Features a 6" discharge and a 6" suction, with an enclosed two vane impeller design that handles up to a 3" solid. Available in all iron and CD4MCu materials. CD4MCu usable in pH's of 2 to 13.5, with Brinell hardness of up to 285. StarTech's patented Cycloseal® design is standard, with a John Crane T-2 single mechanical seal with Viton® elastomers, with stainless steel hardware and tungsten carbide vs. silicon carbide seal faces for abrasion resistance. Bearings are heavy-duty, grease lubricated, deep ball bearings with a minimum of 50,000 hours bearing life.

PARTS	STANDARD MATERIAL (ALL IRON)	CD4MCU
WEAR RINGS	CAST IRON ASTM A48 Class 30	2205 Duplex SS FF ASTM A890
IMPELLER	CAST IRON ASTM A48 Class 30	CD4MCu Cast Stainless ASTM A890 Grade 1A
VOLUTE	CAST IRON ASTM A48 Class 30	CD4MCu Cast Stainless ASTM A890 Grade 1A
SHAFT	1144 Stress Proof Steel	17-4PH Stainless Steel FH -H1075
SHAFT SLEEVE	416 Stainless Steel	316 Stainless Steel

- Superior lift capability
- Excellent NPSHr
- High-efficiency design
- Variable speed
- 24-hour runtime
- Cycloseal® design mechanical seal
- Heavy-duty construction

- **RunDry™ option (Indefinite run dry capability)**
- **Unmanned operations •**  
Redi-Prime® fully automatic self-priming, dry-priming available
- 150 lb. flange on CD4MCu; 125 lb. flange on all iron pump



AGRICULTURE



FOOD



INDUSTRIAL



MINING



MUNICIPAL



OIL & GAS



REFRIGERATION




RENTAL

A typical picture of the pump is shown. Please contact StarTech Pump Company for further details. All information is approximate and for general guidance only.

Feet x .305 = Meters  
Inches x 25.4 = Millimeters  
GPM x .227 = Cubic Meters/Hour  
GPM x 3.785 = Liters/Minute  
HP x .746 = KW

Speed	Impeller Dia.	Style	Solids Dia.	N <sub>s</sub>	Suction	Discharge	No. vanes
VARIOUS	10.09"	ENCLOSED	3.0"	3300	6"	6"	2

SINGLE VOLUTE MOUNTING CONFIG.: CC, VM, F, VF, EM, VC



Performances shown are for each model, close to best efficiency point. Capacity, efficiency and horsepower may vary slightly. Other mounting styles or liquids may require horsepower and/or performance adjustments.

1/15/00

StarTech Pump Company

6NNT - VARIOUS RPM